

# Featured Product Option

Request More Info



## Low Power Consumption Pressure Sensors for Remote or Distributed Installations

### Product Benefits

- Direct connection to lithium battery or solar source
- Configurable to custom needs/designs
- Standard and configurable designs

### Product Features

- Low power consumption – 0.7 mA
- Operates at 3 Vdc
- 0.5 to 2.5 V output
- Quick turn-on time
- Packaging flexibility

Chose a model as a complete sensor

Design a package for your custom product integration



### Available on Models

- GX** General purpose monitoring
- GXR** General purpose monitoring
- GXS** Submersible for murky, sludgy lift station, tanks
- ST** Submersible for clear wells, tanks, ponds
- FH** Flush diaphragm for waste, slurry, adhesive, paint

**OEM pricing and Evaluation samples available on request.**

### Applications

- Oil/gas distributed systems
- Remote pump monitoring & control
- Lift station monitoring & control
- Chemical/process tank farms, storage
- Water/waste water tanks, reservoirs

Contact Dylix to discuss your particular application.



dylixcorp.com • 347 Lang Blvd. Grand Island, NY 14072 USA  
Contact: sales@dylixcorp.com or phone: 716.773.2985

*Bridging the Gap Between Application and Solution<sup>SM</sup>*